according to Regulation GHS (UN)

Trade name: Ceramic Filled-100



SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1 Product identifier:

Trade name: Ceramic Filled-100

1.2 Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses: Photon-curable forming resin for 3D printing. Industrial uses.

Uses advised against: Not for Food additives.

1.3 Details of the supplier of the safety data sheet:

> PANCOLOUR INK CO., LTD. Company:

Address: No. 72-1, Wenming Rd., Guishan Dist., Taoyuan City 33382, Taiwan

Telephone: +886-3-3270177

E-Mail sales1@pancolourink.com

1.4 Emergency telephone number:

Telephone: +886-3-3270177, ext.110

SECTION 2: HAZARDS IDENTIFICATION

2.1 Classification of the substance or mixture:

Classification (Regulation (EC) No. 1272/2008 [CLP]

Acute toxicity(Oral), Cat.5 : H303-May be harmful if swallowed

Skin irritation, Cat.2 : H315-Causes skin irritation

Eye damage, Cat.1 : H318-Causes serious eye damage Skin Sensitization, Cat.1 : H317-May cause an allergic skin reaction

STOT-Repeated exposure, Cat.2 : H373-May cause damage to organs : H412-harmful to aquatic life with long lasting effects

2.2 Label elements

Labelling according to Regulation (EC) No 1272/2008 [CLP/GHS]

Hazard pictograms







Signal word: Danger

Chronic Aquatic hazard, Cat. 3

Hazard H303-May be harmful if swallowed

statements: H315-Causes skin irritation

> H318-Causes serious eye damage H317-May cause an allergic skin reaction

H373-May cause damage to organs H412-harmful to aquatic life with long lasting effects

Precautionary Prevention

P260 Do not breathe dust/fume/gas/mist/vapours/spray. statements:

P261 Avoid breathing dust/fume/gas/mist/vapours/spray.

P264 Wash thoroughly after handling.

P272 Contaminated work clothing should not be allowed out of the workplace.

P273 Avoid release to the environment.

P280 Wear protective gloves/ eye protection/face protection.

Response

P301+ P317 IF SWALLOWED: Get medical help. P302 + P352 IF ON SKIN: Wash with plenty water/...

P305 + P354 + P338 IF IN EYES: Immediately rinse with water for several minutes.

Remove contact lenses, if present and easy to do. Continue rinsing.

P319 Get medical help if you feel unwell.

P332 + P317 If skin irritation occurs: Get medical help. P333 + P317 If skin irritation or rash occurs: Get medical help.

P362 + P364 Take off contaminated clothing and wash it before reuse.

Storage

Disposal

P501 Dispose of contents/container in accordance with local regulation.

according to Regulation GHS (UN)

Trade name: Ceramic Filled-100

Version: 1.1 / EN Revision date: 12.11.2023



2.3 Other hazards

Adverse physicochemical effects: Not available

Adverse human health effects and symptoms: Not available

Adverse environmental effects: Not available

Other adverse hazards: Not available

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.1 **Substances:**

Not applicable.

3.2 **Mixtures**

Description of the mixture:

Viscous Liquid.

Hazardous ingredients

| Substance | Concentration (% w/w) | CAS-No. | Classification regulation 1272/2008/EC, REACH |
|---------------------|--------------------------|-------------|--|
| Acrylated monomer 1 | 5~20% | 52408-84-1 | Acute Tox. 4 *, H302 |
| | | | STOT RE 2 *, H373 ** |
| | | | Eye Dam. 1, H318 |
| | | | Skin Sens. 1, H317 |
| DPGDA | 15~25% | 57472-68-1 | Skin Irrit. 2 , H315 |
| | | | Skin Sens. 1 , H317 |
| | | | Eye Dam. 1 , H318 |
| Acrylated monomer 2 | 1~10% | 48145-04-6 | Eye Dam. 1 , H318 |
| | | | Skin Irrit. 2 , H315 |
| | | | Skin Sens. 1, H317 |
| | | | STOT SE 3 , H335 |
| | | | Aquatic Chronic 2 , H411 |
| Acrylated oligomers | 10~20% | 55818-57-0 | Not applicable |
| TMO | 1~3% | 270586-78-2 | Repr. 2, , H361f |
| Additives | 0.5~1% | 25190-06-1 | Aquatic Chronic 3 , H412 |
| | | | Eye Irrit. 2 , H319 |
| Spherical Alumina | 20~30% | 1344-28-1 | Carc. 2, , H351 |

Additional information:

Full text of H- and EUH-phrases: see SECTION 16.

SECTION 4: FIRST AID MEASURES

4.1 Description of first aid measures

General information: Move the victim to fresh air.

Do not leave the victim unattended.

Move out of dangerous area.

Show this safety data sheet to the doctor in attendance.

If unconscious, place in recovery position and seek medical advice. Following inhalation:

If symptoms persist, call a physician.

Following skin contact: Wash off immediately with soap and plenty of water.

If skin irritation persists, call a physician.

If on skin, rinse well with water. If on clothes, remove clothes.

Following eye contact: Immediately flush eye(s) with plenty of water.

Flush eyes with water as a precaution.

Remove contact lenses.

Keep eye wide open while rinsing.

If eye irritation persists, consult a specialist.

Following ingestion: Keep respiratory tract clear.

Self-protection of the Ensure that medical personnel are aware of the material(s) involved, take first aider:

precautions to protect themselves and prevent spread of contamination

Most important symptoms and effects, both acute and delayed 4.2

according to Regulation GHS (UN)

Trade name: Ceramic Filled-100

Version: 1.1 / EN Revision date: 12.11.2023



May cause an allergic skin reaction. Suspected of damaging the unborn child

Effects Not available

Indication of any immediate medical attention and special treatment needed

This information is not available.

SECTION 5: FIREFIGHTING MEASURES

5.1 Extinguishing media

Suitable extinguishing

Dry sand, ABC powder, Foam

media

Unsuitable extinguishing media High volume water jet.

5.2 Special hazards arising from the substance or mixture

Specific hazards during

Do not allow run-off from fire fighting to enter drains or water courses.

firefighting

Hazardous combustion

Possible decomposition products are: COx, NOx

products

5.3 Advice for fire-fighters

Special protective equipment for fire

fighters

Wear self-contained breathing apparatus for firefighting if necessary.

Further information

Collect contaminated fire extinguishing water separately. This must not be

discharged into drains.

Fire residues and contaminated fire extinguishing water must be disposed

of in accordance with local regulations.

SECTION 6: ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment, and emergency procedures

For non-emergency personnel

Personal precautions Evacuate personnel to safe areas. Use personal protective equipment.

Provide adequate ventilation. Wear appropriate respirator when Protective equipment

ventilation is inadequate. Wear protective gloves/clothing and eye/face

protection.

No action shall be taken involving any personal risk or without suitable Emergency procedures

Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilt material. Do not breathe

vapour or mist.

Personal protective

equipment

If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the

information in "For non-emergency personnel".

For emergency responders

Personal protective equipment

If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the

information in "For non-emergency personnel".

6.2 **Environmental precautions**

> Environmental precautions

Prevent product from entering drains. Prevent further leakage or spillage if safe to do so. If the product contaminates rivers and lakes or drains inform respective authorities.

6.3 Methods and material for containment and cleaning up

For containment Prevent further leakage or spillage if safe to do so.

according to Regulation GHS (UN)

Trade name: Ceramic Filled-100

Version: 1.1 / EN Revision date: 12.11.2023

For cleaning up Soak up with inert absorbent material (e.g. sand, sawdust etc.).

Other information Not available

6.4 Reference to other sections

For personal protection, see section 8.

SECTION 7: HANDLING AND STORAGE

7.1 Precautions for safe handling

Protective measures

Advice on safe Do not breathe vapours/dust. Avoid exposure - obtain special instructions

handling before use. Avoid contact with skin and eyes.

For personal protection see section 8.

Smoking, eating, and drinking should be prohibited in the application area. Dispose of rinse water in accordance with local and national regulations. Persons susceptible to skin sensitisation problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any

process in which this mixture is being used.

Fire preventions Normal measures for preventive fire protection.

Advice on general occupational hygiene

Hygiene measures Do not eat, drink, or smoke when using.

Wash hands before breaks and at the end of workday.

7.2 Conditions for safe storage, including any incompatibilities

Technical measures and storage conditions

Packing materials Original container, plastic containers with cover.

Requirements for storage rooms and vessels

Requirements for Take measures to prevent the build up of electrostatic charge.

storage areas and Use explosion-proof equipment. containers Keep container closed when not in use.

Hints on storage assembly

Storage class Store in original container. Keep containers tightly closed in a cool, well-

ventilated place.

Materials to avoid Keep away from sources of ignition, oxidizing agents, strongly alkaline and

strongly acid materials to avoid exothermic reactions.

Further information on storage conditions

Protect from humidity and water.

7.3 Specific end uses

This information is not available.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1 Control parameters

Biological limit values

| Substance name | CAS-No. | Control parameters | Sampling time | Basis |
|----------------|---------|--------------------|---------------|--------|
| - | - | - | - | TRG903 |

Exposure limits at intended use

Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006:

| Substance name | CAS-No. | End use | Exposure route | Effects | Threshold |
|---------------------|------------|------------|----------------|----------|--------------------------|
| Acrylated monomer 1 | 52408-84-1 | Workers | Inhalation (L) | Systemic | 132.24 mg/m ³ |
| | | | Inhalation (S) | Systemic | 132.24 mg/m ³ |
| | | | Dermal (L) | Systemic | 300 mg/kg bw/day |
| | | | Dermal (S) | Systemic | 300 mg/kg bw/day |
| DPGDA | 57472-68-1 | Workers | Inhalation (L) | Systemic | 24.48 mg/m ³ |
| | | | Dermal (L) | Systemic | 2.77 mg/kg bw/day |
| | | General | Inhalation (L) | Systemic | 7.24 mg/m ³ |
| | | population | | | |
| | | • | Dermal (L) | Systemic | 1.66 mg/kg bw/day |

according to Regulation GHS (UN)

Trade name: Ceramic Filled-100

Version: 1.1 / EN Revision date: 12.11.2023



| Substance name | CAS-No. | End use | Exposure route | Effects | Threshold |
|---------------------|-------------|------------|----------------|----------|------------------------|
| | | | Oral (L) | Systemic | 2.08 mg/kg bw/day |
| Acrylated monomer 2 | 48145-04-6 | Workers | Inhalation (L) | Systemic | 8.22 mg/m ³ |
| | | | Dermal (L) | Systemic | 2.3 mg/kg bw/day |
| | | General | Inhalation (L) | Systemic | 1.4 mg/m ³ |
| | | population | | | |
| | | | Dermal (L) | Systemic | 830 μg/kg bw/day |
| | | | Oral (L) | Systemic | 830 μg/kg bw/day |
| TMO | 270586-78-2 | Workers | Inhalation (L) | Systemic | 822 μg/m³ |
| | | | Dermal (L) | Systemic | 233 μg/kg bw/day |
| | | General | Inhalation (L) | Systemic | 145 μg/m³ |
| | | population | | | |
| | | | Dermal (L) | Systemic | 83.3 μg/kg bw/day |
| | | | Oral (L) | Systemic | 83.3 μg/kg bw/day |

Note: (L)=Long-term; (S)=Short-term

Predicted No Effect Concentration (PNEC) according to Regulation (EC) No. 1907/2006:

| Substance name | CAS-No. | Environment type | Environmental Compartment | Threshold |
|---------------------|-------------|----------------------|---|-------------------------|
| Acrylated monomer 1 | 52408-84-1 | Aquatic Organisms | Freshwater | 12 μg/L |
| | | Aquatic Organisms | Sediment (freshwater) | 9.428 μg/kg sediment dw |
| | | Terrestrial Organism | Soil | 1.442 μg/kg soil dw |
| DPGDA | 57472-68-1 | Aquatic Organisms | Freshwater | 3.4 μg/L |
| | | | Intermittent releases (freshwater) | 34 μg/L |
| | | | Marine water | 340 ng/L |
| | | | Sewage treatment plant (STP) | 100 mg/L |
| | | | Sediment (freshwater) | 8.84 μg/kg sediment dw |
| | | Terrestrial Organism | Soil | 1.3 μg/kg soil dw |
| Acrylated monomer 2 | 48145-04-6 | Aquatic Organisms | Freshwater | 2.7 μg/L |
| | | | Intermittent releases (freshwater) | 27 μg/L |
| | | | Marine water | 270 ng/L |
| | | | Sewage treatment plant (STP) | 10 mg/L |
| | | | Sediment (freshwater) | 177.6 μg/kg sediment dw |
| | | | Sediment (marine water) | 17.8 μg/kg sediment dw |
| | | Terrestrial Organism | Soil | 33.9 μg/kg soil dw |
| TMO | 270586-78-2 | Aquatic Organisms | Freshwater | 1.4 μg/L |
| | | | Intermittent releases (freshwater) | 14 μg/L |
| | | | Marine water | 140 ng/L |
| | | | Intermittent releases (marine water) | 1.4 μg/L |
| | | | Sediment (freshwater) | 115 μg/kg sediment dw |
| | | | Sediment (marine water) | 11.5 μg/kg sediment dw |
| | | Terrestrial Organism | Soil | 22.2 μg/kg soil dw |

8.2 Exposure controls

Appropriate engineering controls

Personal protective equipment

Eye protection: Goggles, Safety glasses

Hand protection: Solvent-resistant gloves (butyl-rubber)

Take note of the information given by the producer concerning $% \left(x\right) =\left(x\right) +\left(x$

permeability and break through times, and of special workplace conditions (mechanical strain, duration of contact). The exact break through time can

be obtained from the protective glove producer and this has to be observed. Please observe the instructions regarding permeability and

according to Regulation GHS (UN)

Trade name: Ceramic Filled-100

Version: 1.1 / EN Revision date: 12.11.2023



breakthrough time which are provided by the supplier of the gloves. Also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion, and the contact time. Recommended preventive skin protection Skin should be washed after contact. The suitability for a specific workplace should be discussed with

the producers of the protective gloves.

Skin and body Choose body protection according to the amount and concentration of the

protection: dangerous substance at the workplace.

Respiratory protection: Use suitable breathing protection if workplace concentration requires.

Environmental exposure controls

Water The product should not be allowed to enter drains, water

courses or the soil.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1 Information on basic physical and chemical properties

| Physical state | Viscous liquid | Odor | Typical arylates |
|--|--------------------------|--|------------------|
| Color | Refer to product label | Odor Threshold | Not available |
| pH | Not applicable | | |
| Melting point / Freezing point | No data available | Initial boiling point / Boiling range | Not available |
| Flash point | > 110°C (Closed-cup) | Evaporation rate | Not available |
| Flammability (Solid, gas) | Not available | Explosive limits | Not available |
| Vapor pressure | Not available | Vapor density | Not available |
| Relative density | 1.4~1.5g/cm ³ | Solubility | Not available |
| Partition Coefficient: n- Octanol/Water | Not available | Auto-ignition temperature | Not available |
| Decomposition Temperature | Not available | Viscosity (25°C) | 400~600cP |

9.2 Other information:

No data available

SECTION 10:STABILITY AND REACTIVITY

10.1 Reactivity

No decomposition if stored and applied as directed.

10.2 Chemical stability

No decomposition if stored and applied as directed.

10.3 Possibility of hazardous reactions

Hazardous reactions: Contact with acids and alkalis may release hydrogen.

Stable under recommended storage conditions.

10.4 Conditions to avoid:

Conditions to avoid High temperature, exposure to direct sun light.

10.5 **Incompatible materials:**

Materials to avoid: Acids, Bases, Oxidizing agents

10.6 Hazardous decomposition products:

Contact with water or

This information is not available.

humidity

Thermal decomposition This information is not available.

SECTION 11:TOXICOLOGICAL INFORMATION

11.1 Information on likely routes on exposure

None known

6/9

according to Regulation GHS (UN)

Trade name: Ceramic Filled-100

Version: 1.1 / EN Revision date: 12.11.2023



11.2 Information on toxicological effects

Acute toxicity

Product: May be harmful if swallowed

Components:

[Acrylated monomer 1] (Oral) Harmful

(Inhalation) LC50 (4 h) 1 mg/L air (rat)

(Dermal) Not classified

Remarks: data from ECHA REACH-dossier information

Skin corrosion/irritation

Product: Causes skin irritation
Components: No data available

Eye damage/irritation

Product: Causes serious eye damage

Components: No data available

Skin/Respiratory sensitization

Product: May cause an allergic skin reaction

Components: No data available

Germ cell mutagenicity

Product: Not classified based on available information.

Components: No data available

Carcinogenicity

Product: Not classified based on available information.

Components: No data available

Reproductive toxicity

Product: Not classified based on available information.

Components: No data available

STOT - Single exposure

Product: Not classified based on available information.

Components: No data available

STOT- Repeated exposure

Product: May cause damage to organs

Components: No data available

Aspiration toxicity

Product: Not classified based on available information.

Components: No data available

SECTION 12: ECOLOGICAL INFORMATION

12.1 Ecotoxicity:

Product: No data available

Components:

【 Acrylated to fish: LC50 (4 days) 2.7 mg/L

monomer 2 to aquatic invertebrates: EC50 (48 h) 158.3 mg/L

to a quatic algae and cyanobacteria: EC50 (72 h) 11.3 - 25.7 mg/L $\,$

to microorganisms: NOEC (14 days) 100 mg/L

Remarks: data from ECHA REACH-dossier information

12.2 Persistence and degradability

Product: No data available

Components:

[Acrylated Biodegradation in water: Inherently biodegradable (100%)

monomer 2]

Remarks: data from ECHA REACH-dossier information

according to Regulation GHS (UN)

Trade name: Ceramic Filled-100

Version: 1.1 / EN Revision date: 12 11 2023

12.3 Bioaccumulative potential

Product: No data available

Components:

Remarks: data from ECHA REACH-dossier information

12.4 Mobility in soil

Product: No data available

Components:

[Acrylated Adsorption/desorption: Koc 141.8 - 621.8 L/kg

monomer 2]

Remarks: data from ECHA REACH-dossier information

12.5 Results of PBT and vPvB assessment

The substances are not considered to be persistent, accumulative, and toxic (PBT). The substances are not considered to be very persistent and very bioaccumulating (vPvB).

12.6 Other adverse effects:

No data available.

SECTION 13: DISPOSAL CONSIDERATIONS

13.1 Waste treatment methods

Product The product should not be allowed to enter drains, water courses or the

> soil. Do not contaminate ponds, water ways or ditches with chemical or used container. Send to a licensed waste management company. In

accordance with local and national regulations.

Contaminated Empty remaining contents. Dispose of as unused product. Do not re-use packaging

empty containers. In accordance with local and national regulations.

SECTION 14:TRANSPORT INFORMATION

14.1 UN number or ID number

Not applicable

14.2 UN Proper shipping name

Not applicable

14.3 Transport hazard class(es)

Not applicable

14.4 Packing group

Not applicable

14.5 Environmental hazards

Not classified as marine pollutant

14.6 Transport in bulk according to IMO instruments

Not applicable for product as supplied.

14.7 Special precautions for user

Not classified as dangerous in the meaning of transport regulations.

14.8 ICAO/IATA -DGR: NOT RESTRICTED AS PER DANGEROUS GOOD

SECTION 15: REGULATORY INFORMATION

15.1 Safety, health, and environmental regulations/legislation specific for the substance or mixture REACH-Candidate List of Substances of Very High Concern for Authorisation (Article 59): Not applicable

15.2 Chemical Safety Assessment

None

SECTION 16:OTHER INFORMATION

according to Regulation GHS (UN)

Trade name: Ceramic Filled-100

Version: 1.1 / EN Revision date: 12.11.2023



Reference

- Globally Harmonized System of Classification and Labelling of Chemicals (GHS), rev.8, 2019
- (EC) No.1272/2008, Annex VI to CLP, ATP14, 2020
- REACH-dossier documents, ECHA
- PBT assessment list, ECHA
- IFA GESTIS International limit values for chemical agents (Occupational exposure limits, OELs)
- TRGS 903 Biological Limit Values (BGW) Technical rule for hazardous substances

Prepared by

Pancolour Ink Co., Ltd. / QA / +886 (3) 3270177

The information provided in this Safety Data Sheet is according to the best of our knowledge and information at the date of its publication. The information in this SDS was obtained from sources, which we believe are reliable. However, the information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal, and release. It is not to be considered a warranty or quality specification. This SDS was prepared and is to be used only for this product. If the product is used as a component in another product, this SDS information may not be applicable.

End of document