PCC PANCOLOUR INK UV CURABLE INK / ADHESIVE / COATING

Trade na	ame Ceramic Fill	ed-200	-	► • ®			
Version:				Revision	n date: 12.11.2023		
SECTION 1.1	I 1: IDENTIFICA Product identifi		ANCE/MIXTURE AND OF THE CO)MPANY/UNDE	ERTAKING		
	Trade name: Cer	ramic Filled-200					
1.2	Relevant identif	fied uses of the substa	ance or mixture and uses advised a	gainst			
	Relevant identifi	ied uses: Photon-cura	ble forming resin for 3D printing. Inc	Justrial uses.			
	Uses advised aga	ainst: Not for Food ad	ditives.				
1.3	Details of the su	pplier of the safety d	ata sheet:				
	Company:	PANCOLOU	IR INK CO., LTD.				
	Address:	No. 72-1, V	Venming Rd., Guishan Dist., Taoyuar	າ City 33382 , Taiາ	wan		
	Telephone: +886-3		/0177				
	E-Mail	<u>sales1@pa</u>	ncolourink.com				
1.4	Emergency tele	phone number:					
	Telephone:	+886-3-327	20177, ext.110				
SECTION	2: HAZARDS II	DENTIFICATION					
2.1		the substance or mix					
	•	egulation (EC) No. 12	· • •				
	Acute toxicity(O		: H303-May be harmful if swal	lowed			
	Skin irritation, C		: H315-Causes skin irritation				
	Eye damage, Cat		: H318-Causes serious eye dar	-			
	Skin Sensitizatio		: H317-May cause an allergic s				
		exposure, Cat.2		-			
	Chronic Aquatic	hazard, Cat. 3	: H412-harmful to aquatic life	with long lasting	effects		
2.2	Label elements Labelling according to Regulation (EC) No 1272/2008 [CLP/GHS]						
	Hazard						
	pictograms	LE W					
	Signal word:	Danger					
	Hazard	H303-May be harm					
	statements:	H315-Causes skin i					
		H318-Causes serio					
			n allergic skin reaction				
		H373-May cause da					
	.		quatic life with long lasting effects				
	Precautionary	Prevention					
	statements:		he dust/fume/gas/mist/vapours/spi	-			
			ing dust/fume/gas/mist/vapours/sp	ray.			
			ghly after handling.				
			d work clothing should not be allow	ed out of the wo	гкріасе.		
			e to the environment.	4 1 ·			
		•	tive gloves/ eye protection/face pro	tection.			
		Response					
			ALLOWED: Get medical help.				
			SKIN: Wash with plenty water/				
			3 IF IN EYES: Immediately rinse with		al minutes.		
			nses, if present and easy to do. Con	tinue rinsing.			
			help if you feel unwell.				
			irritation occurs: Get medical help.				
			i irritation or rash occurs: Get medic	-			
		P362 + P364 Take Storage	off contaminated clothing and wash	it before reuse.			
		-					
		Disposal P501 Dispose of co	ntents/container in accordance with	1 local regulation			
					1/0		



2.3 Other hazards

Adverse physicochemical effects: Not available Adverse human health effects and symptoms: Not available Adverse environmental effects: Not available Other adverse hazards: Not available

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.1 Substances:

Not applicable.

3.2 Mixtures

Description of the mixture:

Viscous Liquid.

Hazardous ingredients

Substance	Concentration (% w/w)	CAS-No.	Classification regulation 1272/2008/EC, REACH
Acrylated monomer 1	5~20%	52408-84-1	Acute Tox. 4 *, H302
			STOT RE 2 *, H373 **
			Eye Dam. 1, H318
			Skin Sens. 1, H317
DPGDA	15~20%	57472-68-1	Skin Irrit. 2 , H315
			Skin Sens. 1 , H317
			Eye Dam. 1 , H318
Acrylated monomer 2	1~8%	48145-04-6	Eye Dam. 1 , H318
			Skin Irrit. 2 , H315
			Skin Sens. 1 , H317
			STOT SE 3 , H335
			Aquatic Chronic 2 , H411
Acrylated oligomers	15~30%	55818-57-0	Not applicable
ТМО	1~3%	270586-78-2	Repr. 2, , H361f
Additives	0.5~1%	25190-06-1	Aquatic Chronic 3 , H412
			Eye Irrit. 2 , H319
Spherical Alumina	20~25%	1344-28-1	Carc. 2, , H351

Additional information:

Full text of H- and EUH-phrases: see SECTION 16.

SECTION 4: FIRST AID MEASURES

4.1	Description of first aid measures					
	General information:	Move the victim to fresh air. Do not leave the victim unattended. Move out of dangerous area. Show this safety data sheet to the doctor in attendance.				
	Following inhalation:	If unconscious, place in recovery position and seek medical advice. If symptoms persist, call a physician.				
	Following skin contact:	Wash off immediately with soap and plenty of water. If skin irritation persists, call a physician. If on skin, rinse well with water. If on clothes, remove clothes.				
	Following eye contact:	Immediately flush eye(s) with plenty of water. Flush eyes with water as a precaution. Remove contact lenses. Keep eye wide open while rinsing. If eye irritation persists, consult a specialist.				
	Following ingestion:	Keep respiratory tract clear.				
	Self-protection of the first aider:	Ensure that medical personnel are aware of the material(s) involved, take precautions to protect themselves and prevent spread of contamination				

4.2 Most important symptoms and effects, both acute and delayed

according to Regulation GHS (UN) Trade name Ceramic Filled-200

Version: 1.1 / EN



Revision date: 12.11.2023

	1	
	Symptoms	Causes skin irritation. May cause an allergic skin reaction. Suspected of damaging the unborn child
	Effects	Not available
4.3	Indication of any immed This information is not a	liate medical attention and special treatment needed vailable.
SECTION	N 5: FIREFIGHTING MEA	ASURES
5.1	Extinguishing media	
	Suitable extinguishing media	Dry sand, ABC powder, Foam
	Unsuitable extinguishing media	High volume water jet.
5.2	Special hazards arising f	rom the substance or mixture
	Specific hazards during firefighting	Do not allow run-off from fire fighting to enter drains or water courses.
	Hazardous combustion products	Possible decomposition products are: COx, NOx
5.3	Advice for fire-fighters Special protective equipment for fire fighters	Wear self-contained breathing apparatus for firefighting if necessary.
	Further information	Collect contaminated fire extinguishing water separately. This must not be discharged into drains. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1 Personal precautions, protective equipment, and emergency procedures For non-emergency personnel					
	Personal precautions	Evacuate personnel to safe areas. Use personal protective equipment.			
	Protective equipment	Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Wear protective gloves/clothing and eye/face protection.			
	Emergency procedures	No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilt material. Do not breathe vapour or mist.			
	Personal protective equipment	If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".			
	For emergency responde	ers			
	Personal protective equipment	If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".			
6.2	Environmental precaution	ons			
	Environmental	Prevent product from entering drains. Prevent further leakage or spillage if			

safe to do so. If the product contaminates rivers and lakes or drains inform

respective authorities. 6.3 Methods and material for containment and cleaning up

precautions

For containment Prevent further leakage or spillage if safe to do so.

Safety Data Sheet

according to Regulation GHS (UN) Trade name Ceramic Filled-200

ade name **Ceramic Fille**

Version: 1.1 / EN



Revision date: 12.11.2023

For cleaning up Soak up with inert absorbent material (e.g. sand, sawdust etc.).

Other information Not available

6.4 Reference to other sections

For personal protection, see section 8.

SECTION 7: HANDLING AND STORAGE

7.1	Precautions for safe ha	Precautions for safe handling						
	Protective measures							
	Advice on safe	Do not breathe vapours/dust. Avoid exposure - obtain special instructions						
	handling	before use. Avoid contact with skin and eyes.						
		For personal protection see section 8.						
		Smoking, eating, and drinking should be prohibited in the application area. Dispose of rinse water in accordance with local and national regulations. Persons susceptible to skin sensitisation problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being used.						
	Fire preventions	Normal measures for preventive fire protection.						
	Advice on general occu	upational hygiene						
	Hygiene measures	Do not eat, drink, or smoke when using.						
		Wash hands before breaks and at the end of workday.						
7.2	Conditions for safe storage, including any incompatibilities							
	Technical measures an	d storage conditions						
	Packing materials	Original container, plastic containers with cover.						
	Requirements for stor	age rooms and vessels						
	Requirements for	Take measures to prevent the build up of electrostatic charge.						
	storage areas and	Use explosion-proof equipment.						
	containers	Keep container closed when not in use.						
	Hints on storage assen	nbly						
	Storage class	Store in original container. Keep containers tightly closed in a cool, well- ventilated place.						
	Materials to avoid	Keep away from sources of ignition, oxidizing agents, strongly alkaline and strongly acid materials to avoid exothermic reactions.						
	Further information or	n storage conditions						
	Protect from humidity	and water.						
7.3	Specific end uses							

This information is not available.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1 Control parameters

Biological limit values

Substance name	Substance name CAS-No. Co		Sampling time	Basis
-	-	-	-	TRG903

Exposure limits at intended use

Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006:

Substance name	CAS-No.	End use	Exposure route	Effects	Threshold
Acrylated monomer 1	52408-84-1	Workers	Inhalation (L)	Systemic	132.24 mg/m ³
			Inhalation (S)	Systemic	132.24 mg/m ³
			Dermal (L)	Systemic	300 mg/kg bw/day
			Dermal (S)	Systemic	300 mg/kg bw/day
DPGDA	57472-68-1	Workers	Inhalation (L)	Systemic	24.48 mg/m ³
			Dermal (L)	Systemic	2.77 mg/kg bw/day
		General	Inhalation (L)	Systemic	7.24 mg/m ³
		population			
			Dermal (L)	Systemic	1.66 mg/kg bw/day

Safety Data Sheet

according to Regulation GHS (UN)

Trade name Ceramic Filled-200

Version: 1.1 / EN



Revision date: 12.11.2023

Substance name	CAS-No.	End use	Exposure route	Effects	Threshold
			Oral (L)	Systemic	2.08 mg/kg bw/day
Acrylated monomer 2	48145-04-6	Workers	Inhalation (L)	Systemic	8.22 mg/m ³
			Dermal (L)	Systemic	2.3 mg/kg bw/day
		General population	Inhalation (L)	Systemic	1.4 mg/m ³
			Dermal (L)	Systemic	830 μg/kg bw/day
			Oral (L)	Systemic	830 µg/kg bw/day
ТМО	270586-78-2	Workers	Inhalation (L)	Systemic	822 μg/m³
			Dermal (L)	Systemic	233 µg/kg bw/day
		General population	Inhalation (L)	Systemic	145 μg/m³
			Dermal (L)	Systemic	83.3 μg/kg bw/day
			Oral (L)	Svstemic	83.3 µg/kg bw/dav

Note: (L)=Long-term; (S)=Short-term

Predicted No Effect Concentration (PNEC) according to Regulation (EC) No. 1907/2006:

Substance name	CAS-No.	Environment type	Environmental Compartment	Threshold
Acrylated monomer 1	52408-84-1	Aquatic Organisms	Freshwater	12 μg/L
		Aquatic Organisms	Sediment (freshwater)	9.428 μg/kg sediment dw
		Terrestrial Organism	Soil	1.442 μg/kg soil dw
DPGDA	57472-68-1	Aquatic Organisms	Freshwater	3.4 μg/L
			Intermittent releases (freshwater)	34 µg/L
			Marine water	340 ng/L
			Sewage treatment plant (STP)	100 mg/L
			Sediment (freshwater)	8.84 μg/kg sediment dw
		Terrestrial Organism	Soil	1.3 μg/kg soil dw
Acrylated monomer 2	48145-04-6	Aquatic Organisms	Freshwater	2.7 μg/L
			Intermittent releases (freshwater)	27 μg/L
			Marine water	270 ng/L
			Sewage treatment plant (STP)	10 mg/L
			Sediment (freshwater)	177.6 μg/kg sediment dw
			Sediment (marine water)	17.8 μg/kg sediment dw
		Terrestrial Organism	Soil	33.9 μg/kg soil dw
TMO	270586-78-2	Aquatic Organisms	Freshwater	1.4 μg/L
			Intermittent releases (freshwater)	14 µg/L
			Marine water	140 ng/L
			Intermittent releases (marine water)	1.4 μg/L
			Sediment (freshwater)	115 μg/kg sediment dw
			Sediment (marine water)	11.5 μg/kg sediment dw
		Terrestrial Organism	Soil	22.2 μg/kg soil dw

8.2 Exposure controls

Appropriate engineering controls Personal protective equipment

Eye protection:

Goggles, Safety glasses

Hand protection:

Solvent-resistant gloves (butyl-rubber)

Take note of the information given by the producer concerning permeability and break through times, and of special workplace conditions (mechanical strain, duration of contact). The exact break through time can be obtained from the protective glove producer and this has to be observed. Please observe the instructions regarding permeability and



Revision date: 12.11.2023

	breakthrough time which are provided by the supplier of the gloves. Also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion, and the contact time. Recommended preventive skin protection Skin should be washed after contact. The suitability for a specific workplace should be discussed with the producers of the protective gloves.
Skin and body protection:	Choose body protection according to the amount and concentration of the dangerous substance at the workplace.
Respiratory protection:	Use suitable breathing protection if workplace concentration requires.
Environmental exposure	e controls
Water	The product should not be allowed to enter drains, water courses or the soil.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1 Information on basic physical and chemical properties

Physical state	Viscous liquid	Odor	Typical arylates
Color	Refer to product label	Odor Threshold	Not available
рН	Not applicable		
Melting point / Freezing point	No data available	Initial boiling point / Boiling range	Not available
Flash point	> 110°C (Closed-cup)	Evaporation rate	Not available
Flammability (Solid, gas)	Not available	Explosive limits	Not available
Vapor pressure	Not available	Vapor density	Not available
Relative density	1.4~1.5g/cm ³	Solubility	Not available
Partition Coefficient: n- Octanol/Water	Not available	Auto-ignition temperature	Not available
Decomposition Temperature	Not available	Viscosity (25°C)	800~1000cP

9.2 Other information:

No data available

SECTION 10: STABILITY AND REACTIVITY

10.1 Reactivity

No decomposition if stored and applied as directed.

10.2 Chemical stability

10.4 Conditions to avoid:

No decomposition if stored and applied as directed.

10.3 Possibility of hazardous reactions Hazardous reactions: Contact with acids and alkalis may release hydrogen.

Stable under recommended storage conditions.

- Conditions to avoid High temperature, exposure to direct sun light.
- **10.5** Incompatible materials: Materials to avoid: Acids, Bases, Oxidizing agents

10.6 Hazardous decomposition products: Contact with water or This information is not available. humidity

Thermal decomposition This information is not available.

SECTION 11: TOXICOLOGICAL INFORMATION

11.1 Information on likely routes on exposure None known

Safety Data Sheet

according to Regulation GHS (UN) Trade name Ceramic Filled-200

Version: 1.1 / EN



Revision date: 12.11.2023

11.2	Information on toxicological effects Acute toxicity				
	Product:	May be harmful if swallov	ved		
	Components:	,			
		[Acrylated monomer 1]	(Oral) Harmful (Inhalation) LC50 (4 h) 1 mg/L air (rat) (Dermal) Not classified		
	Remarks: data from ECHA REACH-dossier information				
	Skin corrosion/irritation				
	Product:	Causes skin irritation			
	Components:	No data available			
	Eye damage/irrita Product:	tion Causes serious eye damag	je		
	Components:	No data available			
	Skin/Respiratory s	ensitization			
	Product:	May cause an allergic skin	reaction		
	Components:	No data available			
	Germ cell mutagenicity				
	Product:	Not classified based on av	ailable information.		
	Components:	No data available			
	Carcinogenicity				
	Product:	Not classified based on av	ailable information.		
	Components:	No data available			
	Reproductive toxicity				
	Product:	Not classified based on av	ailable information.		
	Components:	No data available			
	STOT – Single expo Product:	osure Not classified based on av	ailable information.		
	Components:	No data available			
	STOT- Repeated exposure				
	Product:	May cause damage to org	ans		
	Components:	No data available			
	Aspiration toxicity				
	Product:	Not classified based on av	ailable information.		
	Components:	No data available			
CTION	12:ECOLOGICAL	INFORMATION			
12.1	Ecotoxicity:				
	Product: N	Io data available			

【Acrylated to fish: LC50 (4 days) 2.7 mg/L
monomer 2】 to aquatic invertebrates: EC50 (48 h) 158.3 mg/L
to aquatic algae and cyanobacteria: EC50 (72 h) 11.3 - 25.7 mg/L
to microorganisms: NOEC (14 days) 100 mg/L

Remarks: data from ECHA REACH-dossier information

12.2 Persistence and degradability

Product: No data available

Components:

[Acrylated

Biodegradation in water: Inherently biodegradable (100%)

monomer 2

Remarks: data from ECHA REACH-dossier information



12.3 Bioaccumulative potential

Product: No data available Components:

Remarks: data from ECHA REACH-dossier information

12.4 Mobility in soil

Product: No data available

Components:

[Acrylated Adsorption/desorption: Koc 141.8 - 621.8 L/kg

monomer 2

Remarks: data from ECHA REACH-dossier information

12.5 Results of PBT and vPvB assessment

The substances are not considered to be persistent, accumulative, and toxic (PBT). The substances are not considered to be very persistent and very bioaccumulating (vPvB).

12.6 Other adverse effects:

No data available.

SECTION 13: DISPOSAL CONSIDERATIONS

13.1 Waste treatment methods

Product	The product should not be allowed to enter drains, water courses or the soil. Do not contaminate ponds, water ways or ditches with chemical or used container. Send to a licensed waste management company. In accordance with local and national regulations.
Contaminated packaging	Empty remaining contents. Dispose of as unused product. Do not re-use empty containers. In accordance with local and national regulations.

SECTION 14: TRANSPORT INFORMATION

14.1 UN number or ID number Not applicable
14.2 UN Proper shipping name Not applicable
14.3 Transport hazard class(es) Not applicable
14.4 Packing group Not applicable
14.5 Environmental hazards Not classified as marine pollutant
14.6 Transport in bulk according to IMO instruments Not applicable for product as supplied.
14.7 Special precautions for user Not classified as dangerous in the meaning of transport regulations.
14.8 ICAO/IATA -DGR : NOT RESTRICTED AS PER DANGEROUS GOOD

SECTION 15: REGULATORY INFORMATION

- **15.1** Safety, health, and environmental regulations/legislation specific for the substance or mixture REACH-Candidate List of Substances of Very High Concern for Authorisation (Article 59): Not applicable
- 15.2 Chemical Safety Assessment None

SECTION 16: OTHER INFORMATION

Safety Data Sheet according to Regulation GHS (UN) Trade name Ceramic Filled-200

Version: 1.1 / EN



Revision date: 12.11.2023

Reference	 Globally Harmonized System of Classification and Labelling of Chemicals (GHS), rev.8, 2019 (EC) No.1272/2008, Annex VI to CLP, ATP14, 2020
	- REACH-dossier documents, ECHA
	- PBT assessment list, ECHA
	 IFA GESTIS - International limit values for chemical agents (Occupational exposure limits, OELs) TRGS 903 Biological Limit Values (BGW) Technical rule for hazardous substances
Prepared by	Pancolour Ink Co., Ltd. / QA / +886 (3) 3270177

The information provided in this Safety Data Sheet is according to the best of our knowledge and information at the date of its publication. The information in this SDS was obtained from sources, which we believe are reliable. However, the information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal, and release. It is not to be considered a warranty or quality specification. This SDS was prepared and is to be used only for this product. If the product is used as a component in another product, this SDS information may not be applicable.

End of document